

## **AMENDMENT TO THE CLAIMS**

The following listing of claims replaces all prior listings and versions of claims in this application:

Claims 1. to 5. (Cancelled)

6. (Previously Presented) A tool holder for mounting to a user's clothing article, comprising:

a first support member of an injection-molded material;

a second support member connected to the first support member at a connection portion, wherein the first and second support members are configured and dimensioned for receiving and hooking around the article with the first and second support members disposed on opposite sides of the article, and at least one of the support members comprises a plurality of stiffening ribs extending therefrom and arranged substantially forming a truss that is configured for stiffening said at least one support member; and

a tool holding member mounted to one of the support members and configured for receiving and holding a portion of a handheld tool.

7. (Previously Presented) A tool holder for mounting to a user's clothing article, comprising:

a first support member of an injection-molded material;

a second support member connected to the first support member at a connection portion, wherein the first and second support members are configured and dimensioned for receiving and hooking around the article with the first and second support members disposed on opposite sides of the article; and

a tool holding member mounted to one of the support members and configured for receiving and holding a portion of a handheld tool;

wherein the first support member has a back surface facing away from the second support member and disposed for placement against a user's waist, the back surface having

substantially flat portions surrounding a central area that forms a concave indentation that is curved to generally follow the curve of the user's waist.

8. (Previously Presented) The tool holder of claim 7, wherein:  
the support members are connected to each other and define an article space therebetween configured to receive the article; and  
the first support member has a curved surface facing the article space and disposed to contact the article received therein.

9. (Cancelled)

10. (Withdrawn – Currently Amended) The tool holder of claim ~~[[1]]~~ 6, wherein the tool holding member defines an opening to receive and hold the portion of the tool, the opening being of sufficient size to receive a ~~cylindrical object~~ hand held tool having a diameter of at least about a ½ inch.

11. (Currently Amended) The tool holder of claim ~~[[1]]~~ 7, wherein said one support member comprises a recessed mounting portion for attaching with a correspondingly shaped mounting portion of the tool holding member.

12. (Previously Presented) A tool holder for mounting to a user's clothing article, comprising:

a first support member;

a second support member connected to the first support member at a connection portion, wherein the first and second support members have first ends opposite from the connection portion and have a configuration and are dimensioned for receiving the article through between the first ends and hooking the first and second support members around the article with the first and second support members disposed on opposite sides of the article; and

a tool holding member mounted to the second support member and having an operative position extending from the second support member for receiving and holding a

portion of a hand-held tool and being retractable to a retracted position for decreasing the bulk of the tool holder,

wherein the tool holding member is disposed substantially flush against the second support member in the retracted position such that in the retracted position the holding member is substantially prevented from holding the portion of the tool.

13. (Cancelled)

14. (Original) The tool holder of claim 12, wherein the tool holding member is pivotally connected to the second support member for pivoting between the operative and retracted positions.

15. (Original) The tool holder of claim 14, wherein:  
the second support member comprises a front face facing away from the second support member; and  
the tool holding member is pivotable towards and away from the front face.

16. (Currently Amended) ~~[[A]]~~ The tool holder of claim 10 for mounting to a user's clothing article, further comprising:

~~a first support member;~~

~~a second support member connected to the first support member at a connection portion, wherein the first and second support members are configured and dimensioned for receiving and hooking around the article with the first and second support members disposed on opposite sides of the article, wherein the first and second support members are pieces of separate construction that are joined to each other in a fixed position;~~

~~a tool holding member mounted to the second support member and configured for receiving and holding a portion of a hand-held tool that has a diameter of at least about 1/2 inch;~~  
and

a secondary tool holding member associated with at least one of the support members and tool holding member and configured for holding a second tool.

17. (Previously Presented) The tool holder of claim 16, wherein the secondary tool holding member defines at least one secondary tool recess configured and dimensioned for receiving and holding the secondary tool, and the tool holding portion is configured for holding a handle of the hand-held tool.

18. (Withdrawn) The tool holder of claim 17, wherein the recess has a ribbed, substantially cylindrical portion configured and dimensioned for holding a drill tip.

19. (Withdrawn) The tool holder of claim 18, wherein:  
at least one of the support members defines a grasping recess that is sufficiently large to permit grasping by a user of a portion of a secondary tool disposed therein;  
the secondary tool holding member is disposed for access thereto by the user in the grasping recess;

the grasping recess and secondary tool holding members being configured for holding the secondary tool in the secondary tool holding member with a graspable portion of the secondary tool protruding from the secondary tool holding member and disposed graspably within the grasping recess.

20. (Withdrawn) The tool holder of claim 16, wherein the secondary tool holding member comprises at least one resilient protrusion for engaging a recess of the secondary tool.

21. (Withdrawn) The tool holder of claim 20, wherein the secondary tool holding member comprises a plurality of resilient protrusions configured and dimensioned for engaging a socket for a socket wrench.

22. (Withdrawn) The tool holder of claim 21, wherein the resilient protrusions are movable with respect to each other to accommodate differently sized sockets.

23. (Currently Amended) ~~[[A]] The tool holder of claim 12, for mounting to a user's clothing article, comprising:~~

~~a first support member having a first bottom end and a first connection portion disposed upwards from the first bottom end;~~

~~a second support member having a second bottom end and a second connection portion disposed upwards from the second bottom end, wherein the first and second connection portions are securable to each other in attached association, the first and second support members being configured and dimensioned for receiving the article through between the bottom ends and hooking around the article with the first and second support members disposed on opposite sides of the article, wherein the first and second support members are pieces of separate construction that are joined to each other in a fixed position; and~~

~~a tool holding member mounted to the second support member and configured for receiving and holding a portion of a hand-held tool.~~

24. (Original) The tool holder of claim 23, wherein the connection portions are configured for engagement with each other.

25. (Original) The tool holder of claim 24, further comprising a locking portion associated with the support members for locking the support members together in secured association.

26. (Original) The tool holder of claim 23, wherein:  
at least one of the connecting portions comprises a connecting extension; and  
at least the other of the connecting portions comprises a connecting recess configured to engage the connecting extension for securing the first and second connecting portions to each other.

27. (Original) The tool holder of claim 23, wherein the first and second support members are substantially coupled to each other with the connecting portions in the attached association.

28. (Previously Presented) A tool holder for mounting to a user's clothing article, comprising:

a first support member having a first bottom end and a first connection portion disposed upwards from the first bottom end;

a plurality of second support members, each having a second bottom end and a second connection portion disposed upwards from the second bottom end, wherein the first connection portion is securable to each of the second connection portions in attached association, the first and second support members in the attached association being configured and dimensioned for receiving and hooking around the article with the first and second support members disposed on opposite sides of the article; and

a tool holding member mounted to each of the second support member and configured for receiving and holding a portion of a hand-held tool;

wherein the second support members and tool holders have different configurations for holding different tools.

29. (Withdrawn - Currently Amended) The tool holder of claim [[1]] 12, wherein the second support member has a front face that comprises a recess facing the tool holding member and is configured and dimensioned for receiving another portion of the tool held in the tool holding member.

30. (Withdrawn) The tool holder of claim 29, wherein the tool holding member has a generally rounded portion defining a rounded shape for holding a round portion of the tool, and the recess comprises an indentation in the second support member disposed substantially concentrically with the rounded shape of the tool holding member.

31. (Withdrawn - Currently Amended) The tool holder of claim [[1]] 12, wherein the tool holding member includes a notch configured for receiving and positioning a portion of the tool in a predetermined orientation.

32. (Canceled) ~~[[A]] The tool holder of claim 23, A tool holder for mounting to a user's clothing article, comprising:~~

~~a first support member;~~

~~a second support member connected to the first support member at a connection portion, wherein the first and second support members have first ends opposite from the connection portion and having a configuration and being dimensioned for receiving the article from between the first ends and hooking the first and second support portions around the article with the first and second support members disposed on opposite sides of the article, wherein the first and second support members are pieces of separate construction that are joined to each other in a fixed position; and~~

~~a tool holding member mounted to the second support member and configured for receiving and holding a portion of a hand-held tool;~~

~~wherein at least one of the first and second support members comprises a projection facing the other of the support members for resisting removal of the tool holder from the article.~~

33. (Withdrawn - Currently Amended) The tool holder of claim ~~[[1]]~~ 6, wherein the tool holding member defines a tool space configured for receiving and holding a hand-held tool and first and second openings on opposite sides of and communicated with the tool space, wherein the first opening is larger than the second opening for receiving a larger portion of the tool than the second opening.

34. (Withdrawn - Currently Amended) The tool holder of claim ~~[[1]]~~ 6, wherein the second support member comprises a receiving recess, the holding member mounting portion is received and supported in the recess, and the tool holder further comprises a closure attached adjacent the recess for closing the recess and retaining the holding member mounting portion pivotally therein.

35. (Withdrawn - Currently Amended) The tool holder of claim ~~[[1]]~~ 6, further comprising a mount pivotally attached to the second support member and pivotally

supporting the holding member, wherein the mount has first and second portions disposed about the holding member to trap the holding member in the mount.

36. (Withdrawn - Currently Amended) The tool holder of claim [[1]] 6, further comprising a deflecting ramp disposed adjacent to the mount and configured and angled for deflecting impact from the tool as it is placed moved towards the tool holding member to be held thereby.

37. (Withdrawn - Currently Amended) The tool holder of claim [[1]] 6, wherein the retaining member is in a snap-fit association with the second support member.

38. (Currently Amended) The tool holder of claim [[1]] 6, wherein the tool holding member comprises a generally U-shaped hook member configured for holding an elongated portion of a tool having a diameter of at least about 1/2 inch.

39. (Currently Amended) The tool holder of claim [[1]] 6, wherein the support members are connected to each other and define an article space therebetween configured to receive the article, the first support member having substantially an S-curve shape to define a restricting space portion adjacent the article space, wherein the article space is wider than any restricting facing the restricting portion and the second support member to retain the article in the article space, the first support member curving away from the second support member toward the first end to facilitate insertion of the article from between the first ends.

40. (Currently Amended) The tool holder of claim [[1]] 6, wherein the first and second ends are free ends having a configuration spaced from each other to receive the article therebetween ~~form~~ by hooking the first and second support members around the article.

41. (Currently Amended) The tool holder of claim [[1]] 6, further comprising a tool holding mount that is affixed to the a mounting portion of said one support member, the tool holding member being pivotally mounted to the mount.



42. (Withdrawn) The tool holder of claim 41, wherein the tool holding member is pivotable about two axis with respect to the mount.

43. (Previously Presented) The tool holder of claim 12, wherein the first and second support members are of separate construction.

44. (Previously Presented) The tool holder of claim 7, wherein the first and second support members are pieces of separate construction that are joined in to each other in a fixed position.

45. (Currently Amended) The tool holder of claim [[9]] 6, wherein the first and second support members are pieces of separate construction that are joined in to each other in a fixed position.

46. (New) The tool holder of claim 6, wherein the first and second support members are of injection molded plastic.